

(a) depositing an item inside a deposit accepting machine:

(b) displaying an image of the deposited item through a display operatively connected to the deposit accepting machine, wherein a depositor is provided assurance of the deposit.

23. (newly added) The method according to claim 22 and further comprising capturing an item image of the deposited item inside the deposit accepting machine with an imaging device, and wherein the item image is displayed in (b).

24. (newly added) The method according to claim 23 and further comprising

capturing a depositor image of a depositor with an imaging device, and

displaying the depositor image through the display.

25. (newly added) The method according to claim 24 comprising simultaneously displaying the depositor image and the item image through the display.

26. (newly added) The method according to claim 25 and further comprising

receiving a depositor input through at least one input device in operative connection with the deposit accepting machine, wherein the input includes data associated with the item in (a); and

simultaneously displaying the data, the depositor image, and the item image through the display.

27. (newly added) The method according to claim 24 wherein the item image capturing device has a field of view including an interior area inside the deposit accepting machine, and wherein the depositor image capturing device has a field of view including an exterior area outside of a deposit accepting machine.

28. (newly added) The method according to claim 23 wherein the item image capturing device comprises an infrared camera.

29. (newly added) A method comprising:

(a) receiving a depositor input through at least one input device in operative connection with a deposit accepting machine, wherein the input includes data associated with a deposit item;

(b) depositing the deposit item inside the deposit accepting machine;

- 2/20/03
- (c) displaying the data, a depositor image, and an image of the deposited item through a display operatively connected to the deposit accepting machine.

30. (newly added) The method according to claim 29 wherein (c) includes simultaneously displaying the data, the depositor image, and the deposited item image through the display.